

184 Baker Street • Norman Park, GA 31771 • Phone: (229) 324-3141 • Fax: (229) 324-2226

LUME BRITE

PRODUCT CODE 16100

SIZES AVAILABLE

16100-05 **5 Gallon Pail** • Weighs 50 lbs.

16100-55 **55 Gallon Drum 1 Makes 2 RTU**

• Weighs 510 lbs.

Do not use on glass. Not for use on delicate painted surfaces. Do not allow to dry on surfaces. MUST be diluted into RTU before use and following above recommendations.

KEEP OUT OF REACH OF CHILDREN Do not handle until all safety precautions have been read and understood. Use eye, face, and rubber glove protection when handling these contents. Do not store at temperatures above 120°F. Do not allow to freeze.

TECHNICAL INFORMATION

Color: Brown Odor: Acerbic pH: <=1

Contains Hydrofluoric Acid, Sulfuric Acid



LUME BRITE is a blend of both Hydrofluoric Acid and Sulfuric Acid solutions.

LUME BRITE will leave aluminum with a Satin Sheen appearance when used as directed.

LUME BRITE can be used when anodized or mirror polished surfaces have been damaged beyond restoring. This product can lessen that damaged look.

Optimum dilution of this product is 1 part chemical to 60 parts water when applied downstream with a pressure washer. Used in a pump sprayer, mix 2 ounces of chemical to each 1 gallon of water. In hard water areas more chemical may be required. Always test chemical in an 'out of the way' area. When cleaning with pressure washers, set the metering valve at desired dilution rate, and apply cleaning solution from the bottom up on a dry surface. Always detail clean from the bottom up and rinse from the top down.

DILUTION RATE: Follow optimum dilution using cold water. May be diluted more with hot water.

DO NOT RUN THROUGH PUMPING SYSTEM OR HEATING COILS.